

## Series 0203 Quartering Hammer

### Pictures



### 2. Main technical parameters of product:

Model	020375	020370	020353	020345
Total length (mm)	1200	1200	1200	1200
Total width (mm)	517.8	502.9	530	439
Total height (mm)	1806	1580.7	1471	1018
Diameter of drill rod (mm)	• 75	• 70	• 53	• 45
Operating flow (L/Min)	50-90	40-70	25-50	20-40
Operating pressure (bar)	120-150	110-140	90-120	90-120
Strike frequency (bpm)	400-800	500-900	600-1200	700-1200
Nitrogen chamber pressure (Kg/cm <sup>2</sup> )	12-14	12-14	12-14	12-14
Weight (including hanging parts) (Kg)	566	428	285	183
Applicable model	6-9 t excavator	4-7 t excavator	2.5-4.5 t excavator	1.2-3 t excavator

### Main characteristics of product

1. Machine-mounted hydraulic hammer that can be applied to excavators' and skips' steer loaders.
2. A wide range of functions of the hydraulic hammer can be achieved by using the main equipment system power. Applications: mining, metallurgy, municipal engineering, road engineering, and so on.

Note: HCN products are constantly updated and improved for users. Rights to change the parameters and design are reserved without notifying the users in advance. In case of possible appearance and



## BeyondTech Machinery Co., Ltd.

---

color differences between the products shown in the pictures and the actual products, the actual one shall prevail.