

Series 0305 Disk-type Trencher

I. Picture



II. Main technical parameters of product:

Model	030518	030524
Total width (mm)	1650	1700
Total length (mm)	1640	2000
Total height (mm)	1300	1600
Trenching width (mm)	100	100
Maximum cutting depth (mm)	450	600
Side movement amount (mm)	650	650
Number of cutting heads	40	56
Referring weight (including hanging parts) (Kg)	1100	1200
Allowed maximum pressure (Mpa)	21	21
Operating flow (L/Min)	130-150	130-150



Operating voltage (V) (optional)	DC12/24	DC12/24
Applicable model	Skip steer loader (equipped with large flow output system)	

III. Main characteristics of product

Driven by a skip steer loader with large flow, this product will cut off frozen asphalt pavements. It contains the hard soil layer with gravel, and can be more accurately located compared with a pneumatic or hydraulic quartering hammer. It is an ideal tool in highway curing and municipal construction for pavement repair, arrangement, and paving of water pipes, gas pipes, electric pipes, optical cable pipes, and so on.

1. With the help of electrohydraulic control, the cutting depth and side movement can be adjusted steplessly.
2. The power output of the hydraulic motor with large torque guarantees efficient and easy cutting.
3. The milling cutter tooth and tool apron are of high quality, have a long service life, and offer easier replacement after the cutter tooth is worn and simple and fast replacement of the cutter tooth.
4. Even trenching width and depth and excellent straightness.

Note: HCN products are constantly updated and improved for users. Rights to change the parameters and design are reserved without notifying the users in advance. In case of possible appearance and color differences between the products shown in the pictures and the actual products, the actual one shall prevail.