

Series 0309 Dozer Blade

I. Picture



II. Main technical parameters of product:

Technical parameters of dozer blade				
Model	030960	030972	030984	030996
Total width (mm)	1530	1830	2130	2400
Width in case of rotation of 30° (mm)	1270	1519	1845	2180
Total height (mm)	700	700	700	700
Total length (mm)	965	965	965	965
Maximum swing angle (°)	±30	±30	±30	±30
Maximum swing angle (°)	±10	±10	±10	±10
Weight (including hanging parts) (Kg)	525	556	575	625
Operating flow (L/Min)	20-30	20-30	20-30	20-30
Operating voltage (V) (optional)	DC12/24	DC12/24	DC12/24	DC12/24
Allowed maximum pressure (Mpa)	21	21	21	21
Applicable model	Skip steer loader/small loader			

III. Main characteristics of product



BeyondTech Machinery Co., Ltd.

For land leveling, canal construction, ditch digging, and shoveling of various materials like soil. The adjustable depth guide device allows easier skiving and land leveling. With the strengthened steel structure design, the wear-resistant blade plates at the tail end and the front end can be replaced.

If it is equipped on a small loader, the client shall independently install the position limiter for bucket tilt-back and the skip bucket as per the condition of the main equipment.

Note: HCN products are constantly updated and improved for users. Rights to change the parameters and design are reserved without notifying the users in advance. In case of possible appearance and color differences between the products shown in the pictures and the actual products, the actual one shall prevail.