

## Series T07 Snow-melting Agent Spreader

### I. Pictures



### II. Main technical parameters of product

Table for Technical Parameters of Snow-melting Agent Spreader	
Model	T0701
Total length (mm)	2120
Total width (excluding landing leg) (mm)	1260
Total width (mm)	1500
Transport height (mm)	1300
Total weight (kg)	600
Warehouse material volume (m <sup>3</sup> )	1
Spreading width (m)	0-6 (adjustable)
Spreading amount (g/m <sup>2</sup> )	0-40 (adjustable)
Applicable model	Trucks with the payload mass of 1t and above

### III. Main characteristics of product

1. As automatic snow removal equipment, the snow-melting agent spreader integrates the transshipment, transport, and spreading of snow-melting agent and is widely applied in snow removal from highways, urban roads, airports, squares, and roads in scenic areas. The snow and ice layers on the pavement are easily and



- rapidly removed to ensure safe and smooth road traffic , improve the snow melting speed, and reduce the 1. labor strength. The vehicle-mounted snow-melting agent spreader is characterized by convenient assembly and disassembly, flexibility, and low cost and has been widely used.
2. With the application of the independent gasoline engine, the spreader can be installed easily with high power and improved snow removal efficiency.
  3. With large width, even distribution, and adjustable spreading area, the snow-melting agent spreader will spread by such means as left spreading and right spreading.
  4. The spreading mechanism (projecting disc) can be folded upwards to facilitate emptying of the rest of the snow-melting agent and save storage space.
  5. With a large stock silo volume and filtering device, the snow-melting agent spreader prevents large particles or gathered plates from dropping into the delivery mechanism.
  6. The lower part of the storage silo is designed for reverse V-shaped blanking to make the blanking of the overall storage silo more even.
  7. With simple operation of the complete machine, a single operator can complete all operations in the cab.

Note: HCN products are constantly updated and improved for users. Rights to change the parameters and design are reserved without notifying the users in advance. In case of possible appearance and color differences between the products shown in the pictures and the actual products, the actual one shall prevail.